

CITY OF HOLMES BEACH

BUILDING DEPARTMENT

ROOFING MATERIAL VERIFICATION FORM / PERMIT # _____

OWNER _____ CONTRACTOR _____

JOB ADDRESS _____

SIGNATURE _____ DATE _____

(Contractor / agent)

NUMBER OF SQUARES _____

ROOF SLOPE _____

REMOVE EXISTING YES ___ NO ___

ROOF SLOPE LESS THAN 4 : 12 YES ___ NO ___ FLAT ___
(YES: (2) LAYERS OF 15 LB FELT W/ 19" LAPS MIN. REQ'D.)

UNDERLAYMENT MATERIAL

- 15 LB. ASPHALT FELT - ASTM D 226 TYPE I
- 30 LB ASPHALT FELT - ASTM 226 TYPE II
- SELF-ADHERING MODIFIED BITUMEN - ASTM D 1970
- ASPHALT COATED GLASS FIBER SHEET - ASTM D 4897 TYPE II
- OTHER _____

FASTENER MATERIAL

- NAILS - ASTM F 1667
- PLASTIC TOP NAIL - ASTM A 641
- SPECIALITY NAIL - ASTM D 3161
- TIN TAB NAIL - ASTM A 641
- SCREWS - ASTM A 641
- MORTAR
- ADHESIVE

ROOF VENTS

- RIDGE _____
- OFF RIDGE _____
- SOFFIT ONLY _____
- NONE _____

VALLEY MATERIAL

- ALUMINUM
- GALVANIZED STEEL
- COPPER
- OTHER _____

SYSTEMS / FINISH MATERIALS

- ASPHALT SHINGLES - ASTM D 3462
- ASPHALT SHINGLES - ASTM D 225
- TILE, CONCRETE - ASTM C 1492
- TILE, CLAY - ASTM C 1167
- OTHER - LIST PRODUCT NAME AND ASTM NUMBER
- MINERAL SURFACE ROLL ROOF - ASTM D 224, 249, 371, 3909
- ASPHALT SATURATED ORGANIC FELT BASE SHEET - ASTM D 2626
- ASPHALT COATED ORGANIC FELT BASE SHEET - ASTM D 2626
- ASPHALT COATED ORGANIC PERFORATED - ASTM D 2626
- MINERAL SURFACED INORGANIC CAP SHEET - ASTM D 3809
- MODIFIED BITUMEN, CGSB 37-GP-56M - ASTM D 6162, 6163, 6164
- OTHER - LIST PRODUCT NAME AND ASTM NUMBER

- GALVANIZED STEEL, G-90 ZINC COATED - ASTM A 653
- PREPAINTED STEEL - ASTM A 755
- ALUMINUM ZINC ALLOY COATED STEEL - ASTM A 792
- ALUMINUM - ASTM B 209
- COPPER, 16 OZ PER SQ FT (4.9 KG PER SQ M)
- OTHER - LIST PRODUCT NAME AND ASTM NUMBER
- THERMOPLASTIC SINGLE PLY, CGSB 37-GP-54M, ASTM D 441
- OTHER - LIST PRODUCT NAME AND ASTM NUMBER
- Galvalum 26
- Galvalum 29

WINDBORNE DEBRIS INSPECTION AFFIDAVIT COMPLETED.

An electrical subcontractor (sub-contractor form) is required for any new electrical work including electrical wiring diagrams for all new electrical outlets and disconnects.

A mechanical sub-contractor (sub-contractor form) is required for the removal and re-installation of all mechanical equipment. A separate permit may be required for structural modification.

Re-roofs may be installed over only (1) layer of existing structurally sound materials.

A separate permit may be required for the repair/replacement of damaged sheathing, soffits, etc.

There are (2) or (3) required inspections. Please schedule one day in advance of each inspection.

Option 1 (2 inspections) combination dry-in/flashing with in-progress (less than 50% completion) and final.

Option 2 (3 inspections) roof sheathing nailing, combination dry-in/flashing, in-progress (less than 50% completion) and final.